

MAINTAINING YOUR *FASTLANE* FLOOR



THE FIRST 48 HOURS

Congratulations on your newly coated surface. Here's some important things we'd like you to know about maintaining your Fastlane floor.

Our Polyurea and Polyaspartic resins are industrial grade coatings that cure rather quickly. Like any freshly painted surface it's important to give it proper time to dry without interruption. Be sure to not put your garage door down on it for a minimum of 24 hours! You will know it's ready to walk on if it does not look wet or feel tacky to a touch. You can also do the Hardness Test to determine if it's ready. Waiting 48 hours until heavy items are returned is ideal. Even if it's dry on top, it could still be curing underneath, so we recommend to wait 3-5 days for vehicles to return to the garage.



HARDNESS TEST

Take your fingernail or the handled end of a screwdriver and try pushing it in to the floor in an inconspicuous area. If it doesn't leave a mark or indentation, the floor is ready to walk on.



CLOSING YOUR GARAGE DOOR

Before our departure we manually lower your door to prevent accidental entry but still allow for air circulation. After the 24 hour dry-time period just push your door opener button twice. One push will re-engage the door mechanism, and twice will cycle it to close and/or open. If this doesn't work or there is no response, please check your door sensors on each side of the door near the floor to make sure they are aligned with each other. Fastlane does not alter the functionality of garage doors and is not liable for any malfunctions.

DO'S & DON'T'S

- DO** clean your floor often.
- DO** be mindful of nearby irrigation sources that could compromise your freshly coated surface.
- DO** clean up battery acid, brake fluid, carburetor fluid, pet urine, or any other caustic chemicals immediately.
- DON'T** close your garage door initially for a minimum of 24 hours.
- DON'T** drag super heavy items across the floor without assistance. There is a potential for scuffing from certain items.
- DON'T** introduce water to your coated surface for at least 5 days. This includes rain and/or irrigation.
- DON'T** clean your floor with solvents.

HOW TO CLEAN



Warm soapy water and a mop are all you need. Be sure to squeegee off any excess water after rinsing or cleaning. A deck brush for more vigorous scrubbing can be used if necessary.

The more often you clean your surface, the easier it will be to keep clean. The desert dust settles in quickly, similar to any interior floor, so don't forget to clean your exterior surfaces so you can consistently enjoy their shine!

ANY QUESTIONS? CALL US ANYTIME AT
(702) 660-1218

LOVE YOUR FLOOR?

TELL YOUR FRIENDS AND WE'LL SEND YOU A GIFT CARD WHEN THEY BOOK.

FASTLANE
COATINGS + GARAGE SYSTEMS